

CORNER NOTES

- ① SECTION CORNER SECTIONS 22, 23, 26 & 27, FOUND A STANDARD U.S.F.S. 2 1/2" ALUMINUM MONUMENT WITH 3" CAP IN STONE MOUND REC 21673 1977.
- ② NW 1/4 CORNER SECTIONS 23 & 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 13" PINE S59°45'E 56.5' MKD. NW 1/4 S26 BT, A 16" PINE S62°W 55.6' MKD. NW 1/4 S26 BT.
- ③ 1/4 CORNER SECTIONS 23 & 26, NOT FOUND, ESTABLISHED BY SINGLE PROPORTION, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 10" PINE N44°30'E 20.9' MKD. 1/4 S 23 BT, A 10" PINE S46°30'E 19.0' MKD. 1/4 S26 BT.
- ④ NW 1/4 CORNER SECTION 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 16" PINE N1°E 47.0' MKD. NW 1/4 S26 BT, A 15" PINE S66°5'E 157.6' MKD. NW 1/4 S26 BT.
- ⑤ CN 1/4 CORNER SECTION 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 15" PINE S62°30'W 12.9' MKD. CN 1/4 S26 BT, A 15" PINE N21°5'W 51.7' MKD. CN 1/4 S26 BT.
- ⑥ 1/4 CORNER SECTIONS 26 & 27, RECORD 15"X10"X8" STONE A 36" PINE S69°12'E 41 LKS. A 15" PINE N87°W 118 LKS., FOUND 15"X3"X7" STONE IN STONE MOUND A 50" PINE S69°12'E 41 LKS. WITH PARTIALLY OPENED BLAZE SCRIBING VISIBLE, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 14" FIR N80°30'W 21.5' MKD. 1/4 S 27 BT.
- ⑦ C 1/4 CORNER SECTION 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, NO B.T'S. MKD., CORNER FALLS IN OPEN MEADOW.
- ⑧ CS 1/4 CORNER SECTION 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 10" PINE S82°W 39.7' MKD. CS 1/4 S26 BT, A 9" PINE N16°30'E 20.5' MKD. CS 1/4 S26 BT.
- ⑨ SE 1/4 CORNER SECTION 26, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 19" PINE S83°45'W 49.0' MKD. SE 1/4 S26 BT, A 10" PINE S3°15'W 107.0' MKD. SE 1/4 S26 BT.
- ⑩ 1/4 CORNER SECTIONS 26 & 35, NOT FOUND, ESTABLISHED BY SINGLE PROPORTION SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 8" PINE S2°45'W 27.5' MKD. 1/4 S35 BT, A 10" PINE N77°15'E 18.0' MKD. 1/4 S 26 BT.
- ⑪ E 1/4 CORNER SECTIONS 26 & 35, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 24" PINE S49°45'E 38.8' MKD. E 1/4 S35 BT., A 16" PINE N63°30'E 66.9' MKD. E 1/4 S26 BT.
- ⑫ SECTION CORNER SECTIONS 25, 26, 35 & 36, RECORD POST WITH MOUND AND PITS, FOUND A OLD EMBEDDED MOUND OF STONE IN FENCE LINE FITS RECORD CALLS TO THE SOUTH 2.25' CHS. TO EDGE OF SHAMP AND OVERFLOW LAND, ACCEPTED AS THE CORNER, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 12" PINE S36°W 128.0' MKD. T2AN R146 S35 BT, A 13" PINE N64°W 303.5' MKD. T2AN R146 S26 BT.
- ⑬ 1/4 CORNER SECTIONS 25 & 26, NOT FOUND, ESTABLISHED BY SINGLE PROPORTION SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, NO B.T'S. MKD. CORNER FALLS IN OPEN MEADOW.
- ⑭ CW 1/4 CORNER SECTION 25, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 18" PINE N32°30'E 98.1' MKD. CW 1/4 S25 BT, A 24" PINE S43°20'E 126.1' MKD. CW 1/4 S25 BT.
- ⑮ SW 1/4 CORNER SECTION 25, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 13" PINE S16°15'W 19.4' MKD. SW 1/4 S25 BT., A 15" PINE N17°45'E 19.4' MKD. SW 1/4 S25 BT.
- ⑯ CS 1/4 CORNER SECTION 25, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 13" PINE N19°E 18.1' MKD. CS 1/4 S25 BT, A 13" PINE S78°E 29.3' MKD. CS 1/4 S25 BT.
- ⑰ 1/4 CORNER SECTIONS 25 & 36, RECORD POST WITH MOUND AND PITS, FOUND OLD EMBEDDED MOUND OF STONE IN OLD FENCE LINE FITS RECORD CALL TO THE EAST 9.25' CHS. TO A FAIRLY WELL DEFINED SOUTHWEST SLOPE, ACCEPTED AS THE CORNER, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 12" PINE S30°W 73.1' MKD. 1/4 S36 BT, A 24" PINE N7°W 137.3' MKD. 1/4 S25 BT.
- ⑱ SECTION CORNER SECTIONS 25, 30, 31 & 36, RECORD GRANITE STONE 14"X12"X10" IN STONE MOUND A 54" PINE N40°E 10 LKS., FOUND STONE MOUND AND 53" PINE N40°E 10 LKS. WITH SCRIBING VISIBLE (X N N2 X V E B T), SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 20" PINE S30°30'W 69.4' MKD. T2AN R146 S36 BT, A 10" FIR S57°E 19.0' MKD. T2AN R156 S31 BT.
- ⑲ 1/4 CORNER SECTIONS 25 & 30, RECORD 5" FIR TREE, NOT FOUND, ESTABLISHED BY SINGLE PROPORTION, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 12" FIR S22°30'W 14.7' MKD. 1/4 S25 BT, A 16" FIR N80°E 9.4' MKD. 1/4 S30 BT.
- ⑳ SECTION CORNER SECTIONS 19, 24, 25 & 30, RECORD GRANITE STONE 33"X8"X6" IN STONE MOUND A 8" MAHOGANY N41°12'E 45 LKS., FOUND A STONE MOUND 8'12" DEAD MAHOGANY N41°12'E 45 LKS. SCRIBED T H I V N X V E N X I X B T, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 15" JUNIPER S74°W 22.5' MKD. T2AN R146 S25 BT, A 24" PINE N30°W 121.7' MKD. T2AN R146 S24 BT.
- ㉑ 1/4 CORNER SECTIONS 24 & 25, RECORD 4'X4" POST A 16" PINE N11°W 112 LKS., A 24" FIR S20°W 96 LKS., NOT FOUND, ESTABLISHED BY SINGLE PROPORTION, SET A 3" ALUM. TABLET IN LAVA ROCK, A 10" PINE N74°45'E 126.6' MKD. 1/4 S24 BT, A 23" PINE S72°W 146.8' MKD. 1/4 S25 BT, BRASS TABLET S61°37'W 1.83' MKD. "RM 1.83" → LS 4481 1979"
- ㉒ SECTION CORNER SECTION 23, 24, 25 & 26, RECORD 20"X16"X10" STONE IN A 5'X2' STONE MOUND, THE EVIDENCE FOUND AND BELIEVED TO ACCEPTABLE WAS REJECTED IN THIS SURVEY, IT WAS 465' OUT OF POSITION TO THE NORTH AND NO EVIDENCE OF A 5'X2' STONE MOUND COULD BE FOUND, POSITION ESTABLISH BY DOUBLE PROPORTION.
- ㉓ SECTION CORNER SECTIONS 26, 27, 31 & 35, NOT FOUND, POSITION ESTABLISHED BY DOUBLE PROPORTION.
- ㉔ SECTION CORNER SECTIONS 28, 29, 32 & 33, FOUND A STONE MOUND AND A 41" PINE S66°W 40 LKS. WITH PARTIALY OPEN BLAZE SCRIBING VISIBLE (TXXIV N X V I V E), SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 20" PINE N47°30'E 24.3' MKD. T2AN R146 S 28 BT, A 17" CEDAR S62°E 51.2' MKD. T2AN R146 S33 BT.
- ㉕ 1/4 CORNER SECTIONS 33 T2AN R146 & SECTION 4 T23 N, FOUND A STONE MOUND, A 35" PINE N9°30'W 40 LKS. PARTIALY OPEN BLAZE SCRIBING VISIBLE, A 42" PINE S12°30'W 22 LKS. PREN BURNED BLAZE, SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND.
- ㉖ 1/4 CORNER SECTIONS 35 T2AN R146 & SECTION 2 T23 N, FOUND A STONE MOUND, A 30" PINE S24°E 43 LKS. WITH PARTIALY OPEN BLAZE SCRIBING VISIBLE (1/4 LEGIBLE), SET A STANDARD U.S.F.S. MONUMENT IN STONE MOUND, A 13" FIR N72°W 11.5' MKD. 1/4 S35 BT.
- ㉗ SECTION CORNER SECTIONS 34 & 35 T2AN R146 & SECTIONS 2 & 3 T23 N, NOT FOUND, POSITION ESTABLISHED BY SINGLE PROPORTION.
- ㉘ SECTION CORNER SECTIONS 1 & 2 T2AN R146 & SECTIONS 35 & 36 T25 N, R146, RECORD 22"X17"X9" STONE IN STONE MOUND, A 26" PINE N51°E 34 LKS., 8" PINE N36°1/2'W 90 LKS., A 30" PINE S61°1/2'E 30 LKS., FOUND STONE MOUND, A 18" PINE N35°1/2'W 90 LKS. WITH PARTIALY OPEN BLAZE SCRIBING VISIBLE, 36" PINE S62°E 30 LKS. WITH HEALED BLAZE.

RECORD OF SURVEY

SECTIONS 25 & 26 T. 24 N., R. 14 E., M.D.M.
IN THE UNINCORPORATED AREA OF PLUMAS COUNTY
CALIFORNIA FOR THE UNITED STATES FOREST
SERVICE.

JUNE 1978 & JULY 1979

GLENN A. BERGEY REGISTERED LAND SURVEYOR AAB1