

6 5 CORNER No.1 Record per 7 RS 98 Corner not needed for this survey	T 24 N R 10 E C 1/4 S4 CORNER No.10 Computed corner nothing set	T 24 N R 10 E E 1/16 S4 S9 CORNER No.20 Set 5/8' rebar capped LS 2843 13" Pine S86°W 24.0ft.	T 24 N R 10 E E 1/16 S 9 CORNER No.31 Set 5/8' rebar capped LS 2843 Bearing tree tag on 11" Pine N86°30'E 5.0'	T 24 N R 10 E W 1/16 c-11-c LS 3966 1990 CORNER No.39 Fd. standard USFS Mon. 13" Fir S26°W 16ft Blazed no scribing 11" Fir N40°W 8.0ft. Blazed no scribing
T 24 N R10 E Sec. 32 only 1/4 RCE 22148 1986 CORNER No.2 Fd. standard USFS Mon. Fd. 38" Sugar Pine N11 1/4°E 48.9ft. no scribing 24" Fir S32°W 34.3 ft. no scribing	T 24 N R 10 E E 1/16 S4 CORNER No.11 Set 5/8' rebar capped LS 2843 Bearing tree tag on 13" Sugar Pine is S43°E 25.0 Ft	T 24 N R 10 E 4 3 9 10 LS 3966 1990 CORNER No.21 Fd. standard USFS Mon. 8" Black Oak N24°E 24 ft Blazed no scribing 7" Black Oak S68°E 40 ft Blazed and scribed 12" Black Oak S13°W 36 ft. Blazed no scribing 14" Black Oak N50° W 50 ft Blazed no scribing	T 24 N R 10 E 1/16 S9 S10 CORNER No.32 Set 5/8' rebar capped LS 2843 14" Fir N85°52'W 5.0 ft.	T 24 N R 10 E C 1/4 S11 LS 3966 1990 CORNER No.40 Fd. standard USFS Mon. 11" Cedar N10°E 12.8 ft Blaze Scribed 13" Pine N70°E 12.9 ft. Blazed Scribed
T 25 N R 10 E 32 33 5 4 T 24 N 1970 BLM CORNER No.3 Fd. standard USFS Mon. 16" BLACK OAK DEAD Blazed N 2°W 67 lks	T 24 N R 10 E 1/4 S4 S3 LS 3966 1990 CORNER No.12 Fd. standard USFS Mon. 16" Pine N68°W 28.4 Ft. Blazed and Scribed 20" Sugar Pine N73°E 7.6Ft. Blazed & scribed	T 24 N R 10 E S3 S10 8' to 1/4 cor 1971 CORNER No.22 Fd. standard BLM mon. Witness corner to 1/4 Cor N40°35'22"E 8.3" from cor 24" Pine N47°3/4'W 16 ft Blazed 24" Pine S39°W 24 Lks Blazed	T 24 N R 10 E 1/4 S9 S16 Set tag LS 2843 CORNER No.33 Set 5/8' rebar capped LS 2843 Bearing tree tag on 17" Black Oak N5°18'W 28.8'	T 24 N R 10 E C-W-E 1/64 S 11 LS 3966 1990 CORNER No.41 Fd. standard USFS Mon. 10" Pine S36°E 16.6 ft. Blazed scribed 9" Pine N15°E 11.5 ft Blazed scribed
T 25 N R 10 E S33 1/4 S 4 T 24 N 1970 BLM CORNER No.4 Fd. standard BLM mon. 8" Pine S61°E 781/2 lks Blazed	T 24 N R 10 E SE 1/16 S 4 CORNER No.14 Set 5/8' rebar capped LS 2843 Bearing tree tag on 13" Pine N21°E 25.0 Ft.	T 24 N R 10 E NE 1/16 S9 CORNER No.23 Set 5/8' rebar capped LS 2843 Bearing tree tag on 7" Black Oak N46°W 3 ft	T 24 N R 10 E 1/4 S10 S15 1971 CORNER No.34 Fd. open 3/4" I.P. in 2' X 2' stone mound no BT's	T 24 N R 10 E 1/4 S11 S12 LS 3966 1990 CORNER No.42 Fd. standard USFS Mon. 18" Fir S40°E 32 ft. Blazed no scribing 12" Fir N48 1/4°E 22.7 ft. Blazed no scribing
T 24 N R 10 E NE 1/16 S5 CORNER No.5 Set 5/8' rebar capped LS 2843 Bearing tree tag on 6" Pine, S66°44'E, 15.7'	T 24 N R 10 E S 1/16 S4 S3 LS 3966 1990 CORNER No.15 Fd. standard USFS Mon. 12" Black Oak S52°W 19.0 ft Blazed no scribing 13" Black Oak S87°E 15.0 ft Blazed no scribing	T 24 N R 10 E NW 1/16 S10 CORNER No.24 Set 5/8' rebar capped LS 2843 Bearing tree tag on 24" Pine N50°W 32 ft	T 24 N R 10 E 10 11 15 14 1971 CORNER No.35 Fd. 1/2" IP inside 1" IP tag not legible K tag on 12" Fir, East 6.0'	T 24 N R 10 E NW-SE 1/64 S11 CORNER No.43 Set 5/8' rebar capped LS 2843 Bearing tree tag on 17" Pine S42°E 30.3 ft.
T 24 N R 10 E N 1/16 S5 S4 CORNER No.6 Set 5/8' rebar capped LS 2843 Bearing tree tag on 24" Pine S7°37'W 35.7'	T 24 N R 10 E SW 1/16 S 3 CORNER No.16 Record corner per 9 RS 8	T 24 N R 10 E 1/4 S8 S9 LS5287 1983 CORNER No.25 Set 5/8' rebar capped LS 2843 Bearing tree tag on 13" Pine N34°10'W 42 ft.	T 24 N R 10 E 10 11 15 14 1971 CORNER No.36 Fd. standard BLM mon. 15" Pine N23°E 5lks Blazed no scribing 17" Pine S17°E 34 lks Blazed no scribing 14" Cedar Dead N76°W 41 lks Blazed no scribing	T 24 N R 10 E C-N-SE 1/64 S11 CORNER No.44 Set 5/8' rebar capped LS 2843 Bearing tree tag on 7" Black Oak S12°15'E 15.8 ft.
T 24 N R 10 E 1/4 S6 S5 1989 BLM CORNER No.7 Fd. Standard BLM Mon. 16" Pine N13°48'W 22.2 ft. Blazed, no scribing 13" Black Oak S84°17'W, 28.4 ft. Blazed with scribing	T 24 N R 10 E S5 1/4 S8 LS 2843 1995 CORNER No.17 Fd. standard USFS Mon. Bearing tree tag on 18" Fir N17°40'E 11.5 Ft 28" SUGAR Pine N38°30'E 30 ft. Blazed no scribing	T 24 N R 10 E E 1/16 S9 CORNER No.26 Fd. standard USFS Mon. Bearing tree tag on 9" Sugar Pine S58°W 11 ft Blazed no scribing 19" Sugar Pine S36°E 47.2 ft Blazed and scribed	T 24 N R 10 E 1/4 S9 S10 CORNER No.27 Set 5/8' rebar capped LS 2843 Bearing tree tag on 9" Cedar N15°26'W 6 ft	T 24 N R 10 E 1/4 S10 S11 1971 CORNER No.28 Fd. 3/4" IP LS 3297 No BTs
T 24 N R 10 E E 1/16 S5 CORNER No.8 Set 5/8' rebar capped LS 2843 Bearing tree tag on 14" Pine, N27°E, 25.7 ft.	T 24 N R 10 E S 5 S 4 S 8 S 9 1971 CORNER No.18 Fd. standard BLM mon. 15" Black Oak S 6°E 10 lks Blazed no scribing 7" Black Oak N63°E 25Lks Blazed and scribed 9" black Oak Dead and Down N 29°W 36 Lks Blazed and scribed 36" Pine dead and down S58°W 63 Lks Blazed and scribed	T 24 N R 10 E W 1/16 S10 CORNER No.29 Set 5/8' rebar capped LS 2843 Bearing tree tag on 19" Pine S281°2'E 48 ft	T 24 N R 10 E 1/4 S10 S11 1971 CORNER No.30 Fd. standard BLM mon. 8" Black Oak, N23°W 27lks Blazed no scribing 12" Cedar S88°E 34Lks Blazed no scribing	
T 24 N R 10 E 1/4 S5 S4 2002 LS2843 CORNER No.9 Set 5/8' rebar capped LS 2843 Bearing tree tag on 13" Sugar Pine N83° 49'W 6.8 ft. 12" Pine S63°51'E, 29.4 ft.	T 24 N R 10 E 1/4 S4 S9 1971 CORNER No.19 Fd. standard BLM mon. 26' Sugar Pine N26°E 34 LKS Blazed no scribing 11" Pine S43°E 24.5 Ft B;azed no scribing			

RECORD OF SURVEY for SIERRA PACIFIC INDUSTRIES

A portion of Sections 3,4,5,9,10 & 11
T. 24 N., R. 10 E., M.D.M.

Plumas County ~ California
Scale 1" = 500' Jan, 2003

Hamby Surveying Inc.
P.O. Box 1209
Portola, CA 96122
(530) 832-5571