

T27N R7E 1/4 S22 S27 1975 CORNER No. 2 FD. BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHWEST SLOPE IN FIR AND CEDAR. FD. A 14" WHITE FIR, N82°E, 43.6' REC. A 6" WHITE FIR, N82°E, 66 LKS (BLM 1975) FD. A 25" INCENSE CEDAR, N58°W, 32.3' REC. A 21" CEDAR, N58°W, 49 LKS (BLM 1975) FD. A 17" INCENSE CEDAR, N13°W, 68.6' REC. A 12" INCENSE CEDAR, N13°W, (BLM 1975)	T28N R6E 1/4 S27 S34 1974 CORNER No. 20 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A TIMBERED FLAT, 50'± NORTH OF A PLANTATION. FD. A 20" PONDEROSA PINE, N72°E, 19.1' -HB REC. AN 11" YELLOW PINE, N72°E, 29 LKS (BLM 1974) FD. A 23" PONDEROSA PINE, S30°E, 19.1' -VS REC. 20" YELLOW PINE, S30°E, 29 LKS (BLM 1974)	CORNER NOTES HB = HEALED BLAZE VS = VISIBLE SCRIBING BCIP = BRASS CAPPED IRON PIPE (1) = RECORD PER UNRECORDED SURVEY BY LOREN SARGENT, LS 2322, JAN., 1959 CAF = COLLINS ALMANOR FOREST	
C N 1/16 C S27 LS 4753 2004 CORNER No. 4 SET A 1/2" REBAR WITH A 2" ALUM. CAP. CORNER FALLS IN THE CENTER OF A SMALL CREEK. SCRIBED AN 8" DOUGLAS FIR, S64°W, 16.7' "CN 1/16 S27 BT"	T28N R6E 1/4 S33 S34 1974 CORNER No. 21 FD. BLM BCIP IN A MOUND OF STONE WITH A 3/4" IRON PIPE ALONGSIDE. CORNER FALLS ON TOP OF A RIDGE. FD. A 39" SUGAR PINE, S77 1/4°E, 44.2' -VS REC. A 34" SUGAR PINE, S80°E, 67 LKS (BLM 1974) FD. A 17" WHITE FIR, N89 3/4°W, 22.4' -HB REC. AN 11" WHITE FIR, N89°W, 35 LKS (BLM 1974) FD. A 12" WHITE FIR, N2 1/4°W, 27.6' -HB REC. A 10" WHITE FIR, N4°E, 42 LKS (BLM 1974) FD. A FIR STUMP, S84°W, 39.7' -VS REC. A SUGAR PINE SNAG, S78°W, 41.5 (1)		
T27N R7E S28 S27 1975 CORNER No. 6 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON TOP OF THE NORTH BANK OF A DRY CREEK. FD. A 23" PONDEROSA PINE, N69 3/4°W, 29.0' REC. A 12" YELLOW PINE, N69 3/4°W, 44 LKS (BLM 1975) FD. A 22" PONDEROSA PINE, N87°E, 25.1' REC. A 9" YELLOW PINE, N87°E, 38 LKS (BLM 1975)	T28N R6E 1/4 S34 S35 1974 CORNER No. 22 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON A TIMBERED FLAT. FD. A 28" PONDEROSA PINE, N38°W, 6.3' -HB REC. A 22" YELLOW PINE, N38°W, 9 1/2 LKS (BLM 1974) FD. A 16" PONDEROSA PINE, S71°E, 6.6' -HB POSSIBLE REC. AN 11" PINE, S72°E, 10.5' (1)		
T27N R7E C 1/4 S27 LS 4753 2004 CORNER No. 7 SET A 1/2" REBAR WITH A 2" ALUM. CAP. CORNER FALLS AT THE BASE OF A SLOPE, 15'± EAST OF POWER LINES. SCRIBED A 9" WHITE FIR, N74°E, 31.5' "C 1/4 S27 BT"	LS 2322 CORNER No. 23 FD. A 1" IRON PIPE TAGGED LS 2322 IN A MOUND OF STONE PER (1). CORNER FALLS ON A MODERATE WEST SLOPE IN FIR, PINE AND CEDAR. FD. A 27" WHITE FIR, S14°E, 11.1' -HB REC. A 14" FIR, S18°E, 11.0' (1) FD. A 21" WHITE FIR SNAG, N31°E, 62.6 -HB REC. A 17" FIR, N27°E, 62.6' (1)		
T27N R7E 1/4 27 26 CAF 1957 CORNER No. 8 FD. A CAF 2" ALUM CAP ON A 3/4" ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHWEST SLOPE IN HEAVY TIMBER, 50'± SOUTHEAST OF A RAVINE FLOWING S80°W. FD. A 32" WHITE FIR, S28°44'W, 22.1' -HB REC. A 23" WHITE FIR, S28°W, 33 LKS (CAF) FD. A 13" WHITE FIR, S20°20'E, 37.9' -HB NO RECORD FD. A 36" WHITE FIR, S78°E, 27.1' REC. A 31" WHITE FIR, S78°E, 41 LKS (CAF)	SW 1/16 S34 LS 4753 2004 CORNER No. 24 FD. A 1" IRON PIPE TAGGED LS 2322; OUT OF POSITION, NOT ACCEPTED THIS SURVEY. AT THE TRUE CORNER POSITION: SET A 1/2" REBAR WITH A 2" ALUM CAP FROM WHICH THE ABOVE PIPE BEARS S 76°14'40" E, 5.48'. CORNER FALLS IN A SOMEWHAT FLAT AREA IN THICK FIR AND PINE. SCRIBED A 6" WHITE FIR, S24 1/2°E, 6.8' "SW 1/16 S34 BT"		
T27N R7E S28 S27 S33 S34 1975 CORNER No. 9 FD. A BLM BCIP IN A MOUND OF STONE. CORNER FALLS ON THE NORTHEAST EDGE OF AN OLD ROAD AT THE EDGE OF BUTT LAKE. FD. A 46" SUGAR PINE, N46°W, 60.0' REC. A 38" SUGAR PINE, N40°W, 92 LKS (BLM 1975)	LS 2322 CORNER No. 25 FD. A 1" IRON PIPE TAGGED LS 2322. CORNER FALLS ON THE NORTH SIDE OF A LARGE MEADOW. FD. A TAMARACK SNAG, N36 3/4°W, 13.6' -VS REC. A 13" LODGEPOLE, N37°W, 13.7' (1)		
T27N R7E S27 S26 S34 S35 1975 CORNER No. 11 FD. A BLM BCIP, NO MOUND. CORNER FALLS ON A GENTLY SLOPING NORTH-SOUTH SPUR IN TIMBER. FD. A 23" PONDEROSA PINE, N24°W, 38.9' -HB REC. A 24" SUGAR PINE, N27°W, 60 LKS (BLM 1975) FD. A 27" INCENSE CEDAR, N55°E, 4.6' -VS REC. 27" INCENSE CEDAR, N59°E, 7 LKS (BLM 1975) FD. A 24" SUGAR PINE, S30°E, 4.6' -HB REC. A 22" SUGAR PINE, S22°E, 7 LKS (BLM 1975) FD. A 20" INCENSE CEDAR, S31°W, 6.6' -HB REC. A 19" INCENSE CEDAR, S31°W, 10 LKS (BLM 1975)	R6E LS 4894 T28N 1/4 S34 S3 T27N 1964 CAF CORNER No. 26 FD. A 2" ALUM CAP ON A 1" ALUM ROD PER CAF FIELD NOTES. CORNER FALLS ON A MODERATE WEST SLOPE. FD. A 15" RED FIR, S31°E, 24.7' -HB NO RECORD FD. A 21" WHITE FIR, S22°E, 34.8' -HB REC. A 13" WHITE FIR, S20°E, 53 1/2 LKS (CAF) FD. A 16" WHITE FIR, N40°W, 18.6 -HB NO RECORD		

RECORD OF SURVEY

FOR

ROSEBURG RESOURCES, INC.

"ALMANOR"

IN SECTION 34, T 28 N, R 6 E,
AND IN SECTION 27, T 27 N, R 7 E,
MDM,
IN THE UNINCORPORATED AREA OF
PLUMAS COUNTY,
STATE OF CALIFORNIA

DEL TERRA INC.
SURVEYING
1168 INDUSTRIAL ST.
REDDING, CA 96002
PHONE (530) 241-8050

DATE: JUNE, 2004
SHEET 3 OF 3

13 RS 65