

1. FD. STANDARD BLM MONUMENT NW S30
(7RS91 DELTERRA LS4495)

FWBS:

50PINE S62°32'W, 16.8
(35PINE S64 1/2°W, 15.8-GLO)
40PINE N64°29'W, 39.6
(35PINE N63°W, 39.6-GLO)
22CEDAR, N30°17'W, 24.8
(19CEDAR, N30°1/2'W, 25.0-BLM)
12PINE N75°12'E, 23.6
(10PINE N74 1/2°E, 23.8-BLM)
12PINE S26°53'E, 15.9
(11PINE S27 1/2°E, 15.82)

2. FD. 14"X12"X8" VOLCANIC STONE
REMONUMENTED WITH STANDARD
USFS MONUMENT. NE S30

FWBS:

26"PINE S64°50'E, 45.0'
(9" PINE S65°E, 46.2'-GLO)

SET R.M.- A STANDARD USFS
MONUMENT N8°10'25"E, 70.82'

3. FD. K-TAGS ON NON RECORD TREES
SET STANDARD USFS MONUMENT IN M.O.S.
AT A PROPORTIONAL POSITION. E 1/4 S30

FWBS:

15"PINE S76°14'E, 16.1'
15"B.O. S27°31'E, 32.0'

4. FD. LS2843 (NO RECORD MAP) ACCEPTED
AS THE SOUTHEAST CORNER OF SECTION 30
REMONUMENTED WITH STANDARD USFS
MONUMENT. SE COR S30

FWBS:

35"PINE STUMP S60°24'W, 35.4'
11"PINE S68°45'E, 13.2'
11"PINE S68°02'W, 9.5'

5. FD. STANDARD USFS MONUMENT IN
M.O.S. (LS4435 7RS91) SW COR S30

FWBS:

PINE STUMP N59°W, 33.7'
(43"PINE N61°W, 33.7'-GLO)
PINE STUMP S72°W, 72.6' (SCRIBING)
(52"PINE S76 3/4°E, 72.6'-GLO)
4" PINE N26°E, 47.6' (NEW BT)
3" PINE S59°E, 32.2' (NEW BT)
6" OAK N88°W, 77.5' (NEW BT)

6. FD STANDARD USFS MONUMENT AS
WITNESS CORNER TO TRUE CORNER
POSITION BEARS S0°48'43"E, 4.0'.
(LS4495-7RS91) W 1/4 S30

FWBS:

6" OAK S8°E 68.0'
7" OAK N87°W 33.3'

7. FD STANDARD USFS MONUMENT
(LS4495-7RS91) W 1/4 S31

FWBS:

FD PINE SNAG N40°30'W, 37.6'
(FD SCRIBING)
(40"PINE N40 1/2°W, 37.6'-GLO)
8"FIR N66°E, 5.0'
8"FIR N50°W 7.4'

8. FD PINE STUMP AS PER USFS CORNER
CARDS FITS CORNERS TO SOUTH, EAST,
WEST, AND NORTH. NO ORIG. GLO BTS. SW S31

FWBS:

SET RM STANDARD USFS MONUMENT
N78°19'32"E, 37.87'
SET RM STANDARD USFS MONUMENT
S0°24'18"W, 18.73'
21"FIR N41°10"W, 72.7'

9. SET STANDARD USFS MONUMENT USED
ORIGINAL BEARING TREE FOR CORNER
POSITION. S 1/4 S36, T23N R11E MDM

FWBS:

BROKEN OFF SNAG W/SCRIBING
S53°E, 30.4'
SMALL DEAD PINE N54°E, 77.9'

10. FD 1 1/4" AXLE IN THE MIDDLE OF ROAD. W 1/4 S6

FWBS:

16"FIR (CLOSED FACE) N39°25'W 35.0'
30"PINE (CLOSED FACE) N75°47'E, 70.0'
PINE STUMP S83°31'E, 35.9'
(S83°E, 35.6'-GLO)
PINE STUMP S39°12'W, 31.4'
(S38 1/2°W, 32.3')

11. SET STANDARD USFS MONUMENT
IN MOS. SE COR. S31

FWBS:

26"PINE - CLOSED FACE N44°E, 18.9'
(6"PINE N44 1/4°E 17.8'
9" PINE STUMP HOLE S13°E, 44.6'
(15"PINE S13°E 44.2')
27"PINE - CLOSED FACE S38°W, 25.0'
(25"PINE S38°W 24.5')
22"PINE - CLOSED FACE N32°W, 21.5'
(10"PINE N32 1/2°W, 22.0')

12. FD MARKED ORIGINAL STONE
14"X12"X3"(14"X12"X10" GLO)

FWBS:

17"PINE S40°W, 41.6'
(8"PINE S40°W, 41.6')
32"PINE S58 1/2°E, 34.3'
(14"PINE S58 1/2°E, 34.3')

13. SET STANDARD USFS MONUMENT
C-N-SW-SE 1/256 NO BTS.

14. SET STANDARD USFS MONUMENT
CN-SE-SE 1/256 NO BTS.

15. SET STANDARD USFS MONUMENT
E-E- 1/64 S30/S31 NO BTS

16. SET STANDARD USFS MONUMENT
E 1/16 S30/S31 NO BTS

17. SET STANDARD USFS MONUMENT
C-N-N-NE 1/256 NO BTS

18. SET STANDARD USFS MONUMENT
FOR WC TO NW-NW-NE 1/256 NO BTS
TRUE POSITION IS S1°04'26"E, 153.31'
(TRUE FALLS IN CREEK BED)

19. SET STANDARD USFS MONUMENT
W-W-E 1/256 S30/S31 NO BTS.

20. SET STANDARD USFS MONUMENT
SW-SW-SE 1/256 NO BTS

RECORD OF SURVEY
SECTION 30,31 T22N R12E T24N R9E MDM
PLUMAS COUNTY, CALIFORNIA
FOR
U.S.D.A. FOREST SERVICE
P.O. BOX 11500, QUINCY, CA.

CREW:
B.SNOW
J.SCHMIDT

DRAWN BY: B.SNOW

SHEET 2 OF 2