

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL
R 569
Page 172

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES,
AND
THE SURVEY OF THE SUBDIVISION OF SECTIONS 20 AND 21,
TOWNSHIP 23 NORTH, RANGE 11 EAST,
OF THE
MOUNT DIABLO MERIDIAN
IN THE STATE OF CALIFORNIA

EXECUTED BY
Ronald S. Hamilton, Supervisory Cadastral Surveyor

Under Special Instructions dated and approved September 30, 1982,
which provided for the surveys included under Group No. 827, and
Assignment Instructions dated October 7, 1982, and
Amended Assignment Instructions dated March 16, 1983.

Survey commenced May 11, 1983
Survey completed August 9, 1983

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
REMONUMENTATION OF CERTAIN ORIGINAL CORNERS,
IN
TOWNSHIP 23 NORTH, RANGE 11 EAST,
OF THE
MOUNT DIABLO MERIDIAN
IN THE STATE OF CALIFORNIA

EXECUTED BY
Daniel H. Dierenfield, Surveying Technician

UNDER THE DIRECTION OF
Claude W. Hamon, Supervisory Cadastral Surveyor

Under Special Instructions dated May 27, 1977, approved June 2, 1977,
which provided for the remonumentation included under Group No. 700, and
Assignment Instructions dated May 30, 1978.

Re monumentation commenced June 1, 1978
Re monumentation completed June 21, 1978

45

2		175
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 23 N., R. 11 E., MOUNT DIABLO MERIDIAN, CALIFORNIA		
CHAINS	A root hole, bears N. 5° W., 39 lks. dist., with an uprooted fir snag, 46 ins. diam., lying alongside. At the corner point Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with a magnet at base, and in a mound of stone, 2 1/2 ft. base, to top, with aluminum cap mkd. T23N R11E S21 S22 S28 S27 1983 from which A cedar, 9 ins. diam., bears N. 30 3/4° E., 42 lks. dist., mkd. T23N R11E S22 BT. A cedar, 8 ins. diam., bears S. 44 1/4° E., 47 lks. dist., mkd. T23N R11E S27 BT. A Douglas fir, 16 ins. diam., bears S. 71 3/4° W., 65 lks. dist., mkd. T23N R11E S28 BT. A white fir, 14 ins. diam., bears N. 33 1/2° W., 83 lks. dist., mkd. T23N R11E S21 BT. Cor. is located on a moderate NE slope in moderate growth of cedar, fir, and oak, with dense undergrowth of chaparral.	

37

and local bearing trees

A white fir, 7 ins. diam., bears N. 50° E., 24 lks. dist., mkd. S35 BT.

A white fir, 13 ins. diam., bears S. 12° E., 24 lks. dist., mkd. S2 BT.

A Douglas fir, 11 ins. diam., bears S. 29 1/2° W., 15 lks. dist., mkd. S3 BT.

A Douglas fir, 13 ins. diam., bears N. 15° W., 43 lks. dist., mkd. S34 BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23N R11E
S34|S35
S3|S2
T22N
1978

Deposit the steel rod alongside the iron post.

Cor. is located on a gentle NE slope, 1.00 ch. E of a dirt road, bears N and S.

62

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T23N R11E
S26|S25
S35|S36
1978

from which

An incense cedar, 27 ins. diam., bears N. 9° E., 113 lks. dist., mkd. T23N R11E S25 BT.

A Douglas fir, 8 ins. diam., bears S. 48° E., 78 lks. dist., mkd. T23N R11E S36 BT.

A yellow pine, 26 ins. diam., bears S. 52° W., 44 lks. dist., mkd. T23N R11E S35 BT.

56

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T23N R11E
S23|S24
S26|S25
1978

from which

A Douglas fir, 12 ins. diam., bears N. 51° E., 50 lks. dist., mkd. T23N R11E S24 BT.

An incense cedar, 11 ins. diam., bears S. 5° E., 52 lks. dist., mkd. T23N R11E S25 BT.

An incense cedar, 12 ins. diam., bears S. 43° W., 63 lks. dist., mkd. T23N R11E S26 BT.

A white fir, 11 ins. diam., bears N. 63° W., 38 lks. dist., mkd. T23N R11E S23 BT.

52

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23N R11E
S28|S27
S33|S34
1978

from which

A yellow pine, 18 ins. diam., bears N. 15° E., 49 lks. dist., mkd. T23N R11E S27 BT.

A sugar pine, 10 ins. diam., bears S. 60° E., 48 lks. dist., mkd. T23N R11E S34 BT.

A sugar pine, 12 ins. diam., bears S. 60 1/2° W., 34 lks. dist., mkd. T23N R11E S33 BT.

An incense cedar, 13 ins. diam., bears N. 86° W., 61 lks. dist., mkd. T23N R11E S28 BT.

Cor. is located on a NW slope, 1.50 chs. N of a ridgetop, bears N. 80° E. and S. 80° W.

54

and local bearing trees

A Douglas fir, 13 ins. diam., bears N. 40 1/2° E., 39 lks. dist., mkd. S26 BT.

An incense cedar, 6 ins. diam., bears S. 43° E., 24 lks. dist., mkd. S35 BT.

A Douglas fir, 7 ins. diam., bears S. 9 1/2° W., 30 lks. dist., mkd. S34 BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T23N R11E
S27|S26
S34|S35
1978

from which

A white fir, 13 ins. diam., bears N. 35 1/2° W., 83 lks. dist., mkd. T23N R11E S27 BT.

Deposit the granite stone alongside the iron post.

Cor. is located on the S edge of old logging road, bears N. 64° E. and S. 64° W.

SHEET INDEX

SECTION 11 T23NR11E MDM	1 OF 11
SECTION 6 & 7 T23NR12E MDM	2 OF 11
SECTION 2 T22NR11E MDM	3 OF 11
SECTION 12 T23NR11E MDM	4 OF 11
SECTION 27 & 26 T23NR11E MDM	5 OF 11
SECTION 10 T23NR11E MDM	6 OF 11
CORNER NOTES S11	7 OF 11
CORNER NOTES S6 S7 S12 S2	8 OF 11
CORNER NOTES S27 S26	9 OF 11
CORNER NOTES S10	10 OF 11
BLM FIELD NOTES S27 S26	11 OF 11

RECORD OF SURVEY

SECTIONS 26,27 & 10 T23N R11E, MDM
PLUMAS COUNTY, CALIFORNIA

FOR

U.S.D.A. PLUMAS NATIONAL FOREST
159 LAWRENCE ST
QUINCY, CA. 95971

DRAWN BY: B. SNOW

DATE: DECEMBER, 2011

SHEET 11 OF 11